

## FLEXIBLE HOSES

Dimension in mm - weight gr/m

| DIMENSIONI<br>Ø O. x Ø I. | 2x1 | 2x1,5 | 3x2 | 4x2  | 4x2,5 | 4x3 | 5x3  | 6x4  | 7x5  | 8x5 | 8x6  | 10x6 | 10x7 | 10x8 | 12x8 | 12x10 | 14x10 | 14x12 | 15x12 | 16x12 | 16x14 | 18x15 | 18x16 | 20x16 | 22x18 |  |
|---------------------------|-----|-------|-----|------|-------|-----|------|------|------|-----|------|------|------|------|------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|--|
| <b>PA 6</b>               |     |       |     |      |       |     |      |      |      |     |      |      |      |      |      |       |       |       |       |       |       |       |       |       |       |  |
| Weight                    | 2,8 | 1,6   | 4,5 | 10,8 | 8,8   | 6,5 | 14,5 | 18   | 22   | 35  | 25   | 56   | 46   | 32   | 72   | 40    | 86    | 47    | 70    | 100   | 54    | 90    | 61    |       |       |  |
| Press at 20° ATM          | 56  | 25    | 33  | 56   | 38    | 24  | 42   | 33   | 28   | 38  | 24   | 42   | 29   | 19   | 33   | 15    | 28    | 13    | 19    | 24    | 11    | 15    | 10    |       |       |  |
| Beams of curv.            | 25  | 25    | 25  | 30   | 30    | 30  | 45   | 50   | 62   | 65  | 70   | 75   | 80   | 80   | 100  | 90    | 100   | 120   | 120   | 140   | 200   | 410   |       |       |       |  |
| <b>PA 11 rilsan</b>       |     |       |     |      |       |     |      |      |      |     |      |      |      |      |      |       |       |       |       |       |       |       |       |       |       |  |
| Weight                    | 2,6 | 1,5   | 4,5 | 10   | 7,8   | 6   | 13,5 | 16,5 | 19,5 | 32  | 23,4 | 52   | 43   | 30   | 64   | 36,5  | 78    | 43    | 67    | 93    | 50    | 83    | 56    | 120   | 133   |  |
| Press at 20° ATM          | 66  | 20    | 25  | 66   | 46    | 28  | 50   | 40   | 33   | 46  | 29   | 48   | 35   | 18   | 40   | 17    | 32    | 15    | 20    | 24    | 11    | 16    | 10    | 20    | 18    |  |
| Beams of curv.            | 10  | 20    | 15  | 20   | 20    | 25  | 25   | 35   | 38   | 40  | 40   | 60   | 60   | 60   | 60   | 85    | 80    | 90    | 90    | 95    | 100   | 140   | 350   | 130   | 200   |  |
| <b>PE</b>                 |     |       |     |      |       |     |      |      |      |     |      |      |      |      |      |       |       |       |       |       |       |       |       |       |       |  |
| Weight                    | 2,3 |       |     | 9,1  | 7,3   |     | 12   | 15   | 18   | 30  | 21   | 48   | 39   | 27   | 60   | 33    | 72    |       | 61    | 84    |       |       |       |       | 108   |  |
| Press at 20° ATM          | 21  |       |     | 21   | 15    |     | 16   | 13   | 11   | 15  | 9    | 16   | 11   | 7    | 13   | 6     | 11    |       | 7     | 9     |       |       |       |       | 7     |  |
| Beams of curv.            | 10  |       |     | 18   | 20    |     | 25   | 30   | 35   | 40  | 40   | 55   | 60   | 60   | 60   | 80    | 80    |       | 85    | 100   |       |       |       |       | 150   |  |
| <b>PLU</b>                |     |       |     |      |       |     |      |      |      |     |      |      |      |      |      |       |       |       |       |       |       |       |       |       |       |  |
| Weight                    |     |       |     | 11   | 8,8   |     | 16   | 19   |      | 35  | 29   |      |      | 33   |      |       |       |       |       |       |       |       |       |       |       |  |
| Press at 20° ATM          |     |       |     | 18   | 12    |     | 13   | 11   |      | 12  | 8    |      |      | 7    |      |       |       |       |       |       |       |       |       |       |       |  |
| Beams of curv.            |     |       |     | 20   | 20    |     | 25   | 30   |      | 40  | 35   |      |      | 50   |      |       |       |       |       |       |       |       |       |       |       |  |
| <b>PTFE</b>               |     |       |     |      |       |     |      |      |      |     |      |      |      |      |      |       |       |       |       |       |       |       |       |       |       |  |
| Weight                    |     |       |     | 22   |       |     | 29   | 37   | 44   |     | 51   |      |      | 66   |      | 80    |       | 95    |       |       |       |       |       |       |       |  |
| Press at 20° ATM          |     |       |     | 42   |       |     | 32   | 25   | 21   |     | 18   |      |      | 14   |      | 12    |       | 10    |       |       |       |       |       |       |       |  |

## SPIRAL HOSES IN RILSAN

diameter in mm

Colors range: orange, blue.

Colori on request: natural, red, green, yellow, black.

Working temperature: -20° + 60° C.

| DIMENSION   | LINEAR HOSES | OUT OF WORK | WORK. LENGHT | DIAMETERS      |
|-------------|--------------|-------------|--------------|----------------|
| Ø O. x Ø I. | Lenght m.    | Meters      | Meters       | Inside/outside |
| 4x2         | 10           | 0,40        | 6,5          | 30/38          |
| 6x4         | 30           | 0,95        | 20           | 55/67          |
| 8x6         | 30           | 1           | 20           | 70/86          |
| 10x8        | 30           | 1           | 20           | 90/120         |
| 12x10       | 30           | 1           | 20           | 110/134        |
| 15x12       | 30           | 0,92        | 20           | 150/180        |